



KODAK PROFESSIONAL

Inkjet Smooth Canvas, Matte / 365g

Perfect for high-end gallery wraps

High-quality

KODAK PROFESSIONAL Inkjet Smooth Canvas, Matte / 365g is a smooth, poly/cotton canvas, featuring a 2-over-1 weave and a water-resistant matte inkjet coating, making it the perfect choice for high-end photographic gallery-wraps.

Durable coating

The high-performing inkjet receptive coating is engineered to work with the latest dye and pigmented inks and will not crack when stretched.

FEATURES:

- Poly/cotton blend canvas
- Ultra-smooth, 2-over-1 weave
- Compatible with dye and pigment inks

APPLICATIONS:

- Gallery wraps
- Mounted canvas prints
- Fine art reproduction

US Size	Euro Size	Quantity	SKU
17" x 40'	43,2 cm x 12,19 m	1 Roll	KPROMC17
24" x 40'	61,0 cm x 12,19 m	1 Roll	KPROMC24
36" x 40'	91,4 cm x 12,19 m	1 Roll	KPROMC36
44" x 40'	111,8 cm x 12,19 m	1 Roll	KPROMC44
60" x 40'	154,2 cm x 12,19 m	1 Roll	KPROMC60



KODAK PROFESSIONAL

Inkjet Smooth Canvas, Matte / 365g

Properties	Specifications
Material	65% polyester, 35% cotton base
Fabric Weave	2 x 1 weave
Gauge	18 mil
Base Weight	365g
Whiteness	>105 CEI
Printer/Ink Compatibility	Compatible with all thermal and piezo inkjet printers using water-based dye and pigment-based inks.
Software Setting	The heavyweight coated or matte setting in most RIPs is appropriate; however, we recommend a custom ICC profile for optimal results. Please refer to www.brandmanagementgroup.com for ICC profiles for some printers.
Light Fastness	Inkjet ink fading time is based on the inks you use and print display environment. Dye-based inks fade noticeably under direct sunlight and interior applications where direct sunlight may fall on the image, and/or where fluorescent or other UV lighting is present. Though fading is inherent in all inkjet inks, certain UV-resistant inks, pigment-based inks, and UV-inhibiting coatings will extend image longevity. For light-fastness data and to determine an ink's suitability for the application, contact the ink manufacturer.
Optimal Service Environment	72° F (21° C), 50% R.H. For end use: 0-300° F.
Finishing/Post Processing	No post processing or finishing is required, though a clear fixative may be applied to enhance certain areas of the print.
Handling Recommendations	Avoid touching the coated surface and use cotton gloves when handling inkjet coated materials. Rolls of Kodak inkjet media come with the coated side facing out.
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging
Shelf Life	1 year from the BMG ship date when stored in proper conditions.



KODAK PROFESSIONAL Inkjet Smooth Canvas, Matte / 365g

Product Performance & Suitability: All of the descriptive information and recommendations for the use of Kodak products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by BMG. All Purchasers of Kodak products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor the manufacturer shall be liable either in the tort in contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect in agreement signed by officers of seller and manufacturer.

Eastman Kodak Company 343 State Street Rochester, NY 14650 USA +1-866-563-2533 in North America. Produced using Kodak Technology.
©Kodak, 2017. Kodak, Flexcel, Squarespot, Staccato and the Kodak Logo are trademarks of Kodak.
Subject to technical change without notice. U.FLX.865.0916.en.13

KODAKWFMedia.com

